

Product images	Application	Characteristic	Structure
	► Transportation of category powder particles	► Smooth inner and outer walls	► Color: Transparent
	► Transportation of food liquids	► Good liquidity	► Temperature: -30/+90 °C
	► Gas transportation	► Good airtightness	Can reach +125 °C in a short time
	► Beverages with an alcohol concentration of less than 65°	► Acid alkali resistant, grease resistant	► Standard:
	► are aspirated and excreted	► Wear resistant and hydrolysis resistant	Compliant with the US FDA Food Contact Safety Standards
► Hose wall: Polyether polyurethane	► Food factory	► Does not contain halogens	Compliant with the EU 10/2011 Food Contact Material Standard
► Reinforcement: Stainless steel wire	► Cosmetics industry	► Does not contain phthalate plasticizers	

Part Number	Internal Diameter mm	Outer diameter mm	Weight kg/m	Bending radius mm	Work pressure bar	Bursting Pressure bar	Coil Length m
932U-010-25	10	16	0.140	20	7	0.85	25
932U-012-25	12	18	0.160	25	7	0.85	25
932U-014-25	14	20	0.175	25	7	0.85	25
932U-016-25	16	23	0.190	30	7	0.85	25
932U-018-25	18	25	0.260	32	6	0.85	25
932U-020-25	20	28	0.280	35	6	0.85	25
932U-025-25	25	33	0.450	42	6	0.85	25/30
932U-030-25	30	38	0.540	50	5	0.85	25/30
932U-032-25	32	39	0.580	53	5	0.85	25/30
932U-038-25	38	46	0.750	62	5	0.85	25/30
932U-040-10	40	49	0.800	300	6	0.98	10
932U-051-10	51	61	1.140	350	5	0.98	10
932U-060-10	60	74	1.660	500	5	0.90	10
932U-063-30	63	74.8	1.650	280	3.6	0.70	30

Note: * All technical parameters are approximate values and measured under conditions of 23 °C operating temperature and 50% ambient humidity. They may change accordingly based on actual operating conditions.

* We will periodically revise or adjust the relevant parameters. If we are unable to notify in a timely manner, please forgive us and refer to the data published on the website or company.